

UltraTech Crack Filler
Terms & Conditions (dated 16th March 2022)

A. Areas of Application

UltraTech Crack Filler is an Innovative, Multipurpose, Do-It-Yourself (DIY) solution that can be used to fill surface cracks, joints, gaps and holes on a wide variety of surfaces in your home. It can be used to fill

1. Surface cracks on painted interior walls (e.g., near switchboards, false ceiling, etc.)
2. Surface cracks near joints of wall and another material like wood, tiles, granite, marble, etc. (e.g., around doors, windows, skirtings, kitchen slabs, etc.)
3. Gaps, joints and holes on wooden surfaces, tiles, granite, marbles, and stones (e.g., nail holes on walls; gaps or joints in wooden furniture; gaps in floor tiles or wall tiles; joints like granite slabs and wall, marble skirting and wall, etc.)

UltraTech Crack Filler is water-resistant and can also be used in bathrooms and kitchen.

Kindly refer to the “Conditions of Usage”, “Precautions” and other information furnished below before applying/using the product.

B. Conditions of Usage

- **UltraTech Crack Filler is suitable only for filling narrow surface cracks up to 4mm wide. It is intended for interior use only.** It must not be used for filling big and structural cracks or load bearing cracks/applications.
- In dry weather, UltraTech Crack Filler will take 30 minutes to touch-dry. In wet/humid climate, it may take up to 24 hours to touch-dry. **Let the product dry for 24 hours after applying.**
- Optimum temperature range for using UltraTech Crack Filler is 5° C to 45° C.
- UltraTech Crack Filler is water-resistant (and not waterproof) and can be used fill surface cracks, holes, tile and granite joints in bathrooms and kitchen. However, before applying UltraTech Crack Filler, dry the surface completely.
- Any emulsion based interior paint over UltraTech Crack Filler, once it is fully dry.
- Surface cracks tend to re-appear. Re-apply UltraTech Crack Filler, if needed.
- Joints refer to the common area between two existing surfaces. It does not refer to construction joints.

C. Precautions

- **Shake the tube well before use.**
- **Please test the product on a small area before final application.**
- **UltraTech Crack Filler is suitable only for filling narrow surface cracks up to 4mm wide. It is intended for interior use only.** It must not be used for filling structural cracks or for load bearing cracks/applications.
- UltraTech Crack Filler should not be applied on exterior surfaces, wet surfaces, and glass.
- Do not use UltraTech Crack Filler as an adhesive. However, it can be used to fill gaps between joints, tiles, etc.

- Do not use UltraTech Crack Filler as an electrical insulator. However, it can be used to fill gaps between walls and regular switch board. Care must be taken to ensure that UltraTech Crack Filler does not come in direct contact with electricity.
- Do not perform sanding over UltraTech Crack Filler.
- The Transparent variant turns transparent after 2 days after application.
- **Upon any contact with skin, wash off UltraTech Crack Filler by rubbing with soap and water.**

D. Coverage (under ideal lab conditions)

- 40g/50g pack fills up to 21 feet of cracks 2mm wide and 1mm deep.
- 70g/90g pack fills up to 37 feet of cracks 2mm wide and 1mm deep.

E. Shelf life & Storage

- Best before 24 months from manufacturing date. After opening, use in 6 months for best results.
- Cap bottle tightly and keep in cool and dry place for future use. Clean the applicator with water or cloth after use.
